

VR-L Super

Super-charged LPG reducer up to 300 HP engine power

Part no.: RD.VLS.B

We designed VR-L Super reducer for the most sophisticated engines with high-efficiency output. This reducer is supplied with advanced Liquid Gas Heating System which ensures stable pressure regardless of system temperature. It also has Coil Group Valve built-in so there is no need to install another valve separately.

300 HP
Maximum Power

LGHS
Liquid Gas Heating System

CFD Designed using
Computational Fluid Dynamics

Main features:

- LPG gas type
- Aluminium alloy die cast
- Liquid Gas Heating System
- Working pressure: 1,2 bar (17.4 psi)
- Maximum power: 220 kW (300 HP)
- Working temperature range: -30/+120 °C (-22/+250 °F)
- LPG outlet external diameter: 14 mm
- LPG inlet diameter: 8 mm
- Engine coolant outlet/inlet diameter: 16 mm
- Supplied shut-off valve
- Dimensions: 135x 190x 130 mm / 5.3x7.5x5.1 in
- Body diameter: 100 mm / 4 in
- Dry weight: 1,9 kg (4.2 lbs)
- Approvals: ECE67R01
- **Aluminium water outlet/inlet** available



www.versusgas.com

+48 25 759 42 61

info@versusgas.com

VERSUS[®] FHT
AUTO GAS equipment

FHT Export-Import
ul. Szczecińska 16G
05-300 Minsk Mazowiecki, POLAND