## **VRC-Tauros**

**Dedicated reducer for Sequential CNG Injection Systems** 

Tauros is high power, high performance pressure reducer dedicated to CNG Installations and can be installed in most types of vehicles. The reducer is equipped with sensitive 1-st stage reduction system that warrants stable output pressure regardless of any pressure variation coming from the tank. Thanks to its highly efficient two-stage gas flow control system, the most optimal CNG dosage is achieved in any driving condition.







Part no.: RD.TAU.B

## Main features:

- CNG gas type
- Aluminium alloy die cast
- Working pressure: 1,0-2,5 bar (14.5-36.3 psi)
- Maximum power: 180 kW (250 HP)
- Working temperature range: -30/+120 °C (-22/+250 °F)
- CNG outlet external diameter: 12 mm
- Engine coolant outlet/inlet diameter: 8 mm
- Supplied low-pressure shut-off valve
- Dimensions: 164 x 125 x 105 mm / 6.5 x 4.9 x 4.1 in
- Dry weight: 1,2 kg (2.6 lbs)
- Approvals: ECE110R00, ISO 15500-9





www.versusgas.com

+48 25 759 42 61

info@versusgas.com



VERSUSGAS Sp. z o.o. Debowa 82 05-300 Krolewiec, POLAND