

VRC-Tauros

Dedicated reducer for Sequential CNG
Injection Systems

Part no.: RD.TAU.B

Tauros is high power, high performance pressure reducer dedicated to CNG Installations and can be installed in most types of vehicles. The reducer is equipped with sensitive 1-st stage reduction system that warrants stable output pressure regardless of any pressure variation coming from the tank. Thanks to its highly efficient two-stage gas flow control system, the most optimal CNG dosage is achieved in any driving condition.

250 HP
Maximum Power

CNG
CNG optimized

CFD Designed using
Computational Fluid Dynamics

Main features:

- CNG gas type
- Aluminium alloy die cast
- Working pressure: 1,0 - 2,5 bar (14.5 - 36.3 psi)
- Maximum power: 180 kW (250 HP)
- Working temperature range: -30/+120 °C (-22/+250 °F)
- CNG outlet external diameter: 12 mm
- Engine coolant outlet/inlet diameter: 8 mm
- Supplied low-pressure shut-off valve
- Dimensions: 164x125x105 mm / 6.5x4.9x4.1 in
- Dry weight: 1,2 kg (2.6 lbs)
- Approvals: ECE110R00, ISO 15500-9



www.versusgas.com

+ 48 25 759 42 61

info@versusgas.com

VERSUSGAS
AUTO GAS equipment

VERSUSGAS Sp. z o.o.
ul. Debowa 82
05-300 Krolewicz, POLAND